

### MSHA Approved Single Jacket Mine Fire Hose

Coupled with female and male aluminum rocker lug expansion ring couplings

**Features**

- Outer construction: single jacket, synthetic flame resistant
- Tube construction: flame resistant lining

**Specifications**

- Proof pressure: **500 PSI** at 70°F (21°C)
- Service test pressure: **250 PSI** at 70°F (21°C)
- Working pressure: **225 PSI** at 70°F (21°C)

**Approval**

- Approved by Mine Safety and Health Administration (MSHA) for all mine fire protection applications



Size	Thread	Length	Part #
1-1/2"	NST (NH)	50'	SM515W50RAF
	NPSH		SM515W50RAS

### Double Jacket Potable Water Hose - Blue

**Features**

- Outer construction: double jacket, all polyester
- Tube construction: thermoplastic

**Specifications**

- Proof pressure: **600 PSI** at 70°F (21°C)
- Service test pressure: **300 PSI** at 70°F (21°C)
- Working pressure: **270 PSI** at 70°F (21°C)

**Approval**

- Liner is NSF approved for potable water; fittings are not, except for temporary/emergency drinking needs only

Coupled with female and male, brass or aluminum rocker lug, expansion ring couplings

Size	Thread	Length	Brass Expansion Ring Part #	Aluminum Expansion Ring Part #
1-1/2"	NPSH	50'	PW615B50RBS	PW615B50RAS
		100'	PW615B100RBS	PW615B100RAS
	NST (NH)	50'	PW615B50RBF	PW615B50RAF
		100'	PW615B100RBF	PW615B100RAF
2-1/2"	NPSH	50'	PW625B50RBS	PW625B50RAS
		100'	PW625B100RBS	PW625B100RAS
	NST (NH)	50'	PW625B50RBF	PW625B50RAF
		100'	PW625B100RBF	PW625B100RAF



### 500# All Polyester Rack Hose - UL Labeled



**Application**

- For pin rack service/emergency fire fighting only. Not to be used for washdown

**Materials**

- Outer construction: single jacket, all polyester
- Tube construction: clear thermoplastic

**Specifications**

- Proof pressure: **300 PSI** at ambient temperature 70°F (21°C)
- Service test pressure: **150 PSI** at ambient temperature 70°F (21°C)
- Working pressure: **135 PSI** at ambient temperature 70°F (21°C)

**Approval**

- Underwriters Listed

Coupled with female and male expansion ring couplings

Size	Coupling Type	Length	Folded Part #	Coiled Part #
1-1/2"	pin lug, brass NST (NH)	50'	R515U50PBF/F	R515U50PBF
		100'	R515U100PBF/F	R515U100PBF
	rocker lug, aluminum NST (NH)	50'	R515U50RAF/F	R515U50RAF
		100'	R515U100RAF/F	---

