

Short Crimp Sleeves

Features

- For use with King combination nipples only
- A reliable alternative to band clamps
- Not for use with Dixon® King Crimp® Style shanks



Hose I.D.	Hose O.D.		Sleeve I.D.	Sleeve Wall Thickness	Sleeve Overall Length	Carbon Steel Part #
	From	To				
3/4"	1-5/64"	1-8/64"	1.1875"	.060"	1-1/4"	CSS075-3CS
	1-9/64"	1-12/64"	1.250"	.060"	1-1/4"	CSS075-4CS
	1-17/64"	1-20/64"	1.375"	.060"	1-1/4"	CSS075-6CS
1"	1-21/64"	1-24/64"	1.438"	.060"	1-1/2"	CSS100-3CS
	1-25/64"	1-28/64"	1.500"	.060"	1-1/2"	CSS100-4CS
	1-29/64"	1-32/64"	1.563"	.060"	1-1/2"	CSS100-5CS
	1-33/64"	1-36/64"	1.625"	.060"	1-1/2"	CSS100-6CS
	1-37/64"	1-40/64"	1.688"	.060"	1-1/2"	CSS100-7CS
	1-41/64"	1-44/64"	1.750"	.060"	1-1/2"	CSS100-8CS
	1-41/64"	1-44/64"	1.750"	.060"	1-3/4"	CSS150-1CS
1-1/2"	1-45/64"	1-48/64"	1.813"	.060"	1-3/4"	CSS150-2CS
	1-49/64"	1-52/64"	1.875"	.060"	1-3/4"	CSS150-3CS
	1-53/64"	1-56/64"	1.938"	.060"	1-3/4"	CSS150-4CS
	1-57/64"	1-60/64"	2.000"	.060"	1-3/4"	CSS150-5CS
	1-61/64"	2"	2.063"	.060"	1-3/4"	CSS150-6CS
	2-1/64"	2-4/64"	2.125"	.060"	1-3/4"	CSS150-7CS
	2-5/64"	2-8/64"	2.188"	.060"	1-3/4"	CSS150-8CS
2"	2-9/64"	2-12/64"	2.250"	.060"	1-3/4"	CSS150-9CS
	2-21/64"	2-24/64"	2.438"	.060"	2"	CSS200-3CS
	2-25/64"	2-28/64"	2.500"	.060"	2"	CSS200-4CS
	2-29/64"	2-32/64"	2.563"	.060"	2"	CSS200-5CS
	2-33/64"	2-36/64"	2.625"	.060"	2"	CSS200-6CS
	2-37/64"	2-40/64"	2.688"	.060"	2"	CSS200-7CS
	2-41/64"	2-44/64"	2.750"	.060"	2"	CSS200-8CS
	2-45/64"	2-48/64"	2.813"	.060"	2"	CSS200-9CS
	2-49/64"	2-52/64"	2.875"	.060"	2"	CSS200-10CS
	2-53/64"	2-56/64"	2.938"	.060"	2"	CSS200-11CS
	2-57/64"	2-60/64"	3.000"	.060"	2"	CSS200-12CS
	3"	3-13/64"	3-16/64"	3.313"	.090"	2-5/8"
3-17/64"		3-20/64"	3.375"	.090"	2-5/8"	CSS300-2CS
3-21/64"		3-24/64"	3.438"	.090"	2-5/8"	CSS300-3CS
3-25/64"		3-28/64"	3.500"	.090"	2-5/8"	CSS300-4CS
3-29/64"		3-32/64"	3.563"	.090"	2-5/8"	CSS300-5CS
3-33/64"		3-36/64"	3.625"	.090"	2-5/8"	CSS300-6CS
3-37/64"		3-40/64"	3.688"	.090"	2-5/8"	CSS300-7CS
3-41/64"		3-44/64"	3.750"	.090"	2-5/8"	CSS300-8CS
3-45/64"		3-48/64"	3.813"	.090"	2-5/8"	CSS300-9CS
3-49/64"		3-52/64"	3.875"	.090"	2-5/8"	CSS300-10CS
3-53/64"		3-56/64"	3.938"	.090"	2-5/8"	CSS300-11CS
3-57/64"		3-60/64"	4.000"	.090"	2-5/8"	CSS300-12CS
4"	4-29/64"	4-32/64"	4.563"	.090"	3-15/32"	CSS400-5CS
	4-33/64"	4-36/64"	4.625"	.090"	3-15/32"	CSS400-6CS
	4-37/64"	4-40/64"	4.688"	.090"	3-15/32"	CSS400-7CS
	4-41/64"	4-44/64"	4.750"	.090"	3-15/32"	CSS400-8CS
	4-45/64"	4-48/64"	4.813"	.090"	3-15/32"	CSS400-9CS
	4-49/64"	4-52/64"	4.875"	.090"	3-15/32"	CSS400-10CS
	4-53/64"	4-56/64"	4.938"	.090"	3-15/32"	CSS400-11CS
	4-57/64"	4-60/64"	5.000"	.090"	3-15/32"	CSS400-12CS

