


## U-Series Universal Pneumatic Couplings

## Features:

- temperature range: **-40°F to 250°F (-40°C to 112°C)**
- couplers are automatic
- 2U-Series 6-in-1 (Aro 210, Industrial, Truflate, Lincoln, Italian, and CEJN 320)
- 3U-Series 4-in-1 (ARO 310, Industrial, Truflate, and CEJN 410)
- Parker UC-Series, Hansen Auto-Flo 23, and Tomco Series UC
- Although the universal coupler permits multiple series nipples to mate with one coupler, it is recommended to match like series couplers and nipples. When using a Universal coupler, the lower performance rating between the coupler and nipple must take precedence.
- Some pneumatic applications require the pressurized air to be 'dried' to ensure proper operation of equipment and/or application of product (ie. auto body shops). It is best to match like series couplers and nipples in these applications. If it is necessary to use a Universal coupler, lube the seal and valve area regularly to ensure reliable service.
- for air service only 

## Female Threaded Couplers

Body Size	Threads	Brass Part #
1/4"	1/4" - 18 NPT	<b>2UF2-B</b>
	3/8" - 18 NPT	<b>2UF3-B</b>
3/8"	3/8" - 18 NPT	<b>3UF3-B</b>



## Male Threaded Couplers

Body Size	Threads	Brass Part #
1/4"	1/4" - 18 NPT	<b>2UM2-B</b>
	3/8" - 18 NPT	<b>2UM3-B</b>
3/8"	3/8" - 18 NPT	<b>3UM3-B</b>



## Standard Hose Barb Couplers

Body Size	Hose ID	Brass Part #
1/4"	1/4"	<b>2US2-B</b>
	3/8"	<b>2US3-B</b>
3/8"	3/8"	<b>3US3-B</b>



## Push-On Hose Barb Couplers

Body Size	Hose ID	Brass Part #
1/4"	1/4"	<b>2UB2-B</b>
	3/8"	<b>2UB3-B</b>

