

B73 Compact Filters / Regulators

Pneumatic
Accessories



with transparent bowl



with metal bowl

Features:


- particle removal per ISO 8573-1, Class 5 and Class 3
- pressure range 5-150 PSI
- in-line or modular installation
- 40 micron element
- 3.5 oz. reservoir
- quick-release bayonet bowl
- prismatic lens liquid level indicator
- supplied with GC230 gauge
- inlet pressure:
 - transparent bowl: **150 PSI and 125°F (52°C)**
 - metal bowl: **250 PSI and 175°F (79°C)**

Transparent Bowl


| Port Size | Flow (SCFM) | Automatic Drain Part # | Manual Drain Part # |
|-----------|-------------|------------------------|---------------------|
| 1/4" | 78 | B73G-2AG | B73G-2MG |
| 3/8" | 123 | B73G-3AG | B73G-3MG |
| 1/2" | 123 | B73G-4AG | B73G-4MG |

Metal Bowl and Sight Glass

| Port Size | Flow (SCFM) | Automatic Drain Part # | Manual Drain Part # |
|-----------|-------------|------------------------|---------------------|
| 1/4" | 78 | B73G-2AG-MB | B73G-2MG-MB |
| 3/8" | 123 | B73G-3AG-MB | B73G-3MG-MB |
| 1/2" | 123 | B73G-4AG-MB | B73G-4MG-MB |



1/4 Turn Manual Drain
** minimum clearance required to remove bowl



Automatic Drain
** minimum clearance required to remove bowl

B74 Standard Filters / Regulators



with guard



with metal bowl

Features:


- pressure range 5-150 PSI
- 40 micron element
- 7 oz. reservoir
- relieving type
- supplied with GC230 gauge
- inlet pressure:
 - transparent bowl: **5-150 PSI and 125°F (52°C)**
 - metal bowl: **5-150 PSI and 175°F (79°C)**

Transparent Bowl and Guard


| Port Size | Flow (SCFM) | Automatic Drain Part # | Manual Drain Part # |
|-----------|-------------|------------------------|---------------------|
| 1/2" | 212 | B74G-4AG | B74G-4MG |
| 3/4" | 212 | B74G-6AG | B74G-6MG |

Metal Bowl and Sight Glass

| Port Size | Flow (SCFM) | Automatic Drain Part # | Manual Drain Part # |
|-----------|-------------|------------------------|---------------------|
| 3/8" | 163 | B74G-3AG-MB | B74G-3MG-MB |
| 1/2" | 212 | B74G-4AG-MB | B74G-4MG-MB |
| 3/4" | 212 | B74G-6AG-MB | B74G-6MG-MB |



Manual Drain
** minimum clearance required to remove bowl



Automatic Drain
** minimum clearance required to remove bowl

See pages 422 to 427 for accessories.

! FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings given at 150 PSIG inlet pressure.