




Quick Weld Ferrules

Features:

- 304 stainless construction
- just slip onto sanitary OD tube and weld
- no need to butt weld



| Tube OD | Dimensions | | | 304 Stainless Steel Part # |
|---------|------------|--------|--------|----------------------------|
| | A | B | C | |
| 1" | .290" | 1.005" | .870" | 14QMP-G100 |
| 1½" | .199" | 1.505" | 1.370" | 14QMP-G150 |
| 2" | .205" | 2.005" | 1.870" | 14QMP-G200 |
| 2½" | .210" | 2.505" | 2.370" | 14QMP-G250 |
| 3" | .216" | 3.005" | 2.870" | 14QMP-G300 |
| 4" | .235" | 4.005" | 3.834" | 14QMP-G400 |
| 6" | .321" | 6.005" | 5.782" | 14QMP-G600 |



Sanitary Fittings

Breakaway Coupling - Clamp

Application:

- minimizes spillage and damage associated with pull away and drive away incidents

Materials:

- 316 stainless steel polished to standard $32R_a$, 3A finish
- clamp gasket: EPDM standard, optional material available

Features:

- designed to be installed between a fixed point and a hose
- 13kN break load bolts standard, other break loads available
- coupling breaks away with an excessive load
- other sizes/connection available



Specification:

- working pressure: **350 PSI @ 70°F (21°C)**

| Size | 316 Stainless Steel Part # |
|------|----------------------------|
| 2" | SBC-E200CC13 |
| 3" | SBC-E300CC13 |

