

Steel Hose Cabinet

FM

Features:

- red polyester coated finish on 18-gauge steel
- designed for wall installation, with or without legs, or free standing
- supplied with holes in the back for wall mounting and 1" pipe couplings on the bottom for adding legs
- Factory Mutual approved
- hose, accessories and mounting hardware not included
- furnished without legs, if legs required contact Dixon®

Fire Fittings & Accessories



Steel

Part #

HC30143

Dimensions

width	depth	height
60"	15"	48"

Basic Approved Equipment for Hose Cabinet

Examples			Quantity Required		
Part #	Description	Page #	Factory Mutual	UL & FIA	ISO
A525-50RAF ¹	2½" x 50' single jacket hose	733	4	5	5
A515-50RAF ¹	1½" x 50' single jacket hose	733	2	0	0
UPP250F ¹	Underwriters play pipe	750	0	2	2
BFN250NST ¹	2½" adjustable fog nozzle	752	2	0	0
BFN150NST ¹	1½" adjustable fog nozzle	752	1	0	0
HA2515F ¹	2½" x 1½" pin lug adapter	771	1	0	0
233	universal spanner	799	4	5	5
189	adjustable hydrant wrench	800	2	2	2
PHFA6	6 lb. fire axe	820	0	1	1
FCB48	crowbar	---	0	1	1
SW150 ¹	1½" hose coupling gasket	741, 742, 754, 785	4	5	5
SW250 ¹	2½" hose coupling gasket	741, 742, 754, 785, 792	2	0	0

¹ threads must be appropriate to the authority having jurisdiction