

Turbo Nozzles

Features:

- 15° spray angle
- temperatures to **195°F**
- ceramic orifice




Part #	Description	Orifice	Nozzle Size	Max. Operating PSI	Price/E
AL-TPR25-30	¼" female inlet, yellow	1.30 mm	4.0	3,625	\$182.30
AL-TPR25-50	¼" female inlet, green	1.50 mm	5.5 - 6.0	3,625	182.30
AL-TPR25-70	¼" female inlet, red	1.70 mm	7.0 - 7.5	3,625	182.30
AL-TPR30-30	¼" female inlet, yellow	1.30 mm	4.0	5,075	276.25
AL-TPR30-50	¼" female inlet, green	1.50 mm	5.5	5,075	276.25
AL-TPR30-70	¼" female inlet, red	1.70 mm	6.5	5,075	276.25

Nozzle Holders

G



AL414



AL416

Features:

- temperatures to **300°F**

Part #	Description	GPM	Operating PSI	Price/E
AL414	adjustable hi/low nozzle holder with nozzle protector, ¼" female inlet and outlet	7.8	3,650	\$47.25
AL416	change over nozzle, ¼" female inlet, 2 each ¼" female outlet	8	2,900	63.30

Inlet Filter for Turbo Nozzles

Features:

- ¼" female inlet, ¼" male outlet
- temperatures to **212°F**
- 100 mesh filter



Part #	Description	GPM	Operating PSI	Price/E
AR3500	stainless steel, inlet water filter	8	5,000	\$37.50

Braided Rubber Hose



Part #	Pressure PSI	Length	Inside Diameter	Male Swivel Inlet	Male Swivel Outlet	Price/E
AR503830SSP	4,000	50'	3/8"	3/8"	3/8"	\$242.65

Hand Crank Hose Reel

Features:

- operating PSI: **3,000 PSI**
- temperature to: **160°F**
- 3/8" male outlet
- steel
- 3/8" female inlet
- holds 100' of 3/8" pressure hose



Part #	Price/E
AR-REEL 100	\$397.80