


## Pipe Fittings

### NPT Threaded Square Head Plugs

**Features**

- Brass plugs are solid
- Lead-free brass per NSF/ANSI 372

Male NPT- <b>SAE</b>	Lead-Free Brass 260/270 Part #	Optional Qty
1/8"	2110200C	100
1/4"	2110400C	100
3/8"	2110600C	25
1/2"	2110800C	25
3/4"	2111200C	25
1"	2111600C	10



### Hex Head Plugs

NPTF	Brass		Pkg Qty	Lead-Free Brass <sup>1,2</sup> Part #	316 Stainless Steel <sup>3</sup> Part #
	Previous Part #	Part #			
1/8"	HHP1M	1630200C	50	1630200CLF	1630200SS
1/4"	HHP2M	1630400C	100	1630400CLF	1630400SS
3/8"	HHP3M	1630600C	25	1630600CLF	1630600SS
1/2"	HHP4M	1630800C	25	1630800CLF	1630800SS
3/4"	HHP6M	1631200C	25	1631200CLF	1631200SS
1"	HHP8M	1631600C	10	1631600CLF	1631600SS



brass



316 stainless steel

- <sup>1</sup> Lead-free brass <=0.25% lead; Alloy CA2745; Alloy C46400  
<sup>2</sup> Conforms To: Safe Water Drinking Act (SWDA) of Jan. 4, 2014; California AB1953; RoHS Compliant  
<sup>3</sup> NPT thread  
 NOTE: Standard brass hex head plug is hollow; lead-free brass and stainless steel are solid

### Hex Socket Plugs

**Feature**

- Lead-free brass per NSF/ANSI 372

NPTF	Lead-Free Brass 260/270		Opt Qty	316 Stainless Steel <sup>1</sup> Part #
	Previous Part #	Part #		
1/8"	219-0200	2190200C	50	2190200SS
1/4"	219-0400	2190400C	100	2190400SS
3/8"	219-0600	2190600C	25	2190600SS
1/2"	219-0800	2190800C	25	2190800SS
3/4"	219-1200	2191200C	25	2191200SS
1"	--	2191600C	10	2191600SS



brass



316 stainless steel

- <sup>1</sup> NPT thread  
 NOTE: For additional information on pipe dimensions please reference [dixonvalve.com](http://dixonvalve.com).

## LockNLube® Grease Coupler

**Application**

- Fits all DIN and SAE specification Zerk fittings (grease nipples)

**Features**

- Works on all grease fittings, SAE, and metric
- Works with all grease gun types - pneumatic, manual, and electric
- Lock-on mechanism - four hardened steel jaws are resilient under high-pressure
- Will not leak once locked on, grease goes in the machine and will clear most clogged fittings
- Hands-free, does not release under pressure
- Easy release thumb lever disconnects with ease
- Free rebuild kit included with every LockNLube grease coupler

**Material**

- Seal - durable nitrile seal for longevity under high-pressure

**Specification**

- Rated up to **10,000 PSI**

Size	Length	Width	Height	Diameter (Front Coupler)	Part #
1/8" NPT	3-1/2"	5/8"	1-7/8"	5/8"	LLGC18
	5-1/2"	3/5"	1-3/5"	5/8"	LLGC18XL



LLGC18



LLGC18XL