# GSM Ball-Joint Armored Hydraulic Assemblies

The Right Connection®

A flexible, rugged hydraulic hose solution suitable for tough applications



Better Resistance To Impact, Abrasion, and Kinking

# **Application**

 Ideal for hydraulic service in abrasive environments requiring protection from external abuse, extreme heat, and severe kinking

### Sizes

1/4" through 2-1/2" standard, other sizes are available

### **Feature**

 Other options available: high temp hose, non-conductive thermoplastic hose, and high pressure GAM hose (GSM Armored Metal hose)

# **Materials**

- · Tube: oil resistant, synthetic rubber
- · Reinforcement: 2 wire braid
- · Insulation: fiberglass
- GSM Ball-Joint Armour: carbon steel and stainless steel

## **Specifications**

- Specification: 100R2, 100R12, 100R13
- Heat resistant insulation to 1000°F
- Temperature: rate depends on specific application, consult Dixon Specialty Products for details

Hose ID	Working Pressure			Bend Radius		
	100R2	100R12	100R13	100R2	100R12	100R13
1/4"	5800	n/a	n/a	3"	n/a	n/a
3/8"	5000	4000	n/a	4"	5"	n/a
1/2"	4250	4000	n/a	6"	7"	n/a
5/8"	2750	4000	n/a	7"	8"	n/a
3/4"	2125	4000	5000	8-1/2"	9-1/2"	9-1/2"
1"	2500	4000	5000	10"	12"	12"
1-1/4"	2250	3000	5000	14-1/2"	16-1/2"	16-1/5"
1-1/2"	1800	2500	5000	18"	20"	20"
2"	1300	3000	5000	22"	25"	25"

© 2021 DVCC • GSMBJAHA\_1021



225 Talbot Blvd. Chestertwon, MD, 21620 ph: 888.226.4673 fx: 410.778.1958 dixonvalve.com